



**TEST REPORT**  
**IEC TR 62778**

**Application of IEC 62471 for the assessment of blue light hazard to  
light sources and luminaires**

Report Reference No.....: EED31K002109

Compiled by (+ signature).....: Carrie Lin

Reviewed by (+ signature).....: Torres He

Approved by (+ signature).....: Amo Liu

Lab Supervisor

Date of issue.....






**Summary of testing:**

**Test conditions:**

1. Ambient temperature: 24,8 ; Humidity: 53%;
2. Measurement distance: 200mm;
3. Aperture stop: 7mm

**Spectral Distribution**







IEC TR 62778			
Clause	Requirement + Test	Result - Remark	Verdict
<b>7</b>	<b>MEASUREMENT INFORMATION FLOW</b>		P
<b>7.1</b>	<b>Basic flow</b>		N/A
	'Law of conservation of luminance' applied		N/A
	Use of only true luminance/radiance values		N/A
	In case of luminaire: The light source is operated in the luminaire under similar conditions as when tested as a component		N/A
	In case $E_{thr}$ value for RG2 was established the peak value was derived from angular light distribution		N/A
<b>7.2</b>	<b>Conditions for the radiance measurement</b>		P
	Standard condition applied (200mm distance, 0,011rad field of view)		P
	Non standard condition applied		N/A



IEC TR 62778

Clause	Requirement + Test	Result - Remark	Verdict
--------	--------------------	-----------------	---------

TABLE: Spectroradiometric measurement			P
Measurement performed on:	<input checked="" type="checkbox"/> LED package <input type="checkbox"/> LED module <input type="checkbox"/> Lamp <input type="checkbox"/> Luminaire		
Model number.....	2835-HCL		
Test voltage (V).....	3,02		
Test current (mA).....	60		
Test frequency (Hz).....	N/A		
Ambient, t (°C).....	24,8		
Measurement distance.....	<input checked="" type="checkbox"/> 20 cm <input type="checkbox"/> cm		

Item	Symbol	Units	Result
------	--------	-------	--------



Photo Document

